

Technical Data Sheet



EASYSAIL 40

DESCRIPTION

| | |
|-----------------|------------------|
| Fabric | 9017 |
| Finish | Polyurethane |
| Yarn | PA 6.6 - 33 dtex |
| Width | 152 cm |
| Pattern | Rip Stop |
| Internal ref. | 90171520E72xxx |
| Length of rolls | 150 lm |



Utilization / End-uses

Cruising spinnaker

Technical Specifications

| Characteristics | | Test Method | Unit | Tolerance | |
|------------------------|--------------|-----------------|--------------------------------------|--------------|--------|
| Coated fabric's weight | | ISO 2286-2 | g/sqm | 41 \pm 2 | |
| | | | oz | 0,96 | |
| Tear Strength | warp | NFG 07-145 | Lbs | 3,0 min | |
| | weft | | | 3,0 min | |
| Elongation | under 20 Lbs | Internal Method | 1/100 inch | 17-31 | |
| | | | | Bias | 20 max |
| | | | | Warp Fill | 30 max |
| Breaking strength | warp | ISO 1421 | DaN/5 cm | 35 mini | |
| | weft | | | 33 mini | |
| Air porosity | | ISO 9237 | l/sqm/mn under 2000 Pa surface 100cm | 100 maxi | |

| | Development Department | Commercial Department | Quality Department |
|-----------|------------------------|-----------------------|--------------------|
| Approvals | | | |



OKAN d.o.o. Ilovac 29
 Karlovac Croatia 47000
 M.: +385996666789
 T.: +38547615917
 www.okandoo.com
 info@okandoo.com