

SPINRACE 50



DESCRIPTION

Fabric : 70026
Yarn : Nylon
Width : 152 cm
Pattern : Ripstop
Internal ref. : 700261520C07xxx
Length of rolls : 150 lm



END USES

FOR RACING PERFORMANCE

Grand Prix racers and fast cruisers looking for performance and durability.

Exceptional burst and tear strength allow lighter cloth in stronger winds.

High density weave and unique coating chemistry maximize wind propulsion and long-lasting low porosity.

Double ripstop for high tear strength in handling and touching rough edges.

Ideal for stability of asymmetric sails constructions.

Technical Specifications

	Characteristics	Test method	Unit	Tolerance
Coated fabric's weight		ISO 2286-2	g/sqm oz	55 1.28
Tear strength	Warp Weft	NGF 07-145	Lbs	5.5 mini 4 mini
Tensile strength	Warp Weft	ISO 1421	DaN/5 cm	55 mini 50 mini
Elongation Under 20lbs	Bias Warp Weft	Internal Method	1/100 inch	14.5 max 17.5 max 31.5 max
Air Porosity		ISO 9237	L/sqm/min under 2000 Pa surface 100cm ²	100 max

Indice : 0

Date : 11/12/2023

porcher **SPORT**®

The information contained in this specification is based on our current experience, values quoted are given for guidance purpose only. PORCHER SPORT reserve themselves the right to proceed to any modification aiming to improve the quality of their products. This document belongs exclusively to PORCHER SPORT. The reproduction is strictly forbidden.